

iCube 

Makes trends compatible.

USB2.0 CMOS CAMERAS - INDUSTRIAL AND OEM VERSION

net 
NEW ELECTRONIC TECHNOLOGY

iCube - MAKES TRENDS COMPATIBLE

iCube – a challenge in performance & price.




iCube USB2.0 SERIES

NET has designed an easy to use compact camera with USB interface. iCube is dedicated for the integration into professional factory automation, quality inspection, surveillance and non-industrial applications like biometrics and microscopy. iCube cameras are equipped with the latest available high performance CMOS image sensors to offer the best image quality achievable with camera process electronic.

The iCube series supports monochrome and color image sensors, allowing a wide selection of resolutions and selectable frame rates. Furthermore the iCube series is offered as industrial and board level version. Fast connection and power via USB port makes the iCube series a universal plug and play camera linked with a notebook, a PC or even for an embedded computer system.

A single cable connection, no additional power supply devices and inexpensive cabling turn iCube into a flexible and fast to implement solution.

The included viewer software iControl allows a quick implementation, access and handling of all iCube cameras at once.



TECHNICAL DATA – CMOS CAMERA LINE

PRODUCT OVERVIEW

iCube supports monochrome and color image sensors, allowing a wide selection of resolutions and selectable frame rates. iCube is offered as small sized and lightweight industrial and board level version. The CMOS image sensors provide an excellent image quality and are equipped with global shutter for fast moving objects and rolling

shutter, also with global reset image readout, to capture images with outstanding signal quality. iCube offers multiple free scalable regions of interest (ROI). Due to its enhanced image sensor sensitivity, the camera realizes a high quantum efficiency and thus is a perfect fit for applications in the near infrared region.

The benefits of a USB interface with low power consumption combined with CMOS technology make the iCube series a precise camera for easy and quick implementation in various applications.

INDUSTRIAL	NS1044BU	NS1044CU	NS1130BU	NS1130CU	NS4133BU	NS4133CU	NS4133IR	NS1201CU	NS4203BU	NS4203CU	NS1300CU	NS1500BU	NS1500CU	NS11000BU	NS11000CU			
BOARD	KS1044BU	KS1044CU	KS1130BU	KS1130CU	KS4133BU	KS4133CU	KS4133IR	KS1201CU	KS4203BU	KS4203CU	KS1300CU	KS1500BU	KS1500CU	KS11000BU	KS11000CU			
Resolution (H x V) [px]	752 x 480 / WVGA		1280 x 1024 / SXGA		1280 x 1024 / SXGA			1600 x 1200 / UXGA	1600 x 1200 / UXGA		2048 x 1536 / QXGA		2592 x 1944 / QSXGA		3840 x 2748 / WQXGA			
Sensor	CMOS		CMOS		CMOS			CMOS	CMOS		CMOS		CMOS		CMOS			
Image sensor	MT9V032		MT9M001	MT9M131	EV76C560		EV76C661	MT9D131	EV76C570		MT9T001	MT9P031	MT9P001	MT9J003				
Sensor size	1/3"		1/2"	1/3"	1/1.8"			1/3.2"		1/1.8"		1/2"		1/2.5"		1/2.3"		
Pixel size [µm]	6.00 x 6.00		5.20 x 5.20		3.60 x 3.60		5.30 x 5.30		2.80 x 2.80		4.50 x 4.50		3.20 x 3.20		2.20 x 2.20		1.67 x 1.67	
Frame rate [fps]	86		25					25	15		20		11		6		3	
Shutter	global		rolling		global; rolling; global reset			rolling		global; rolling; global reset		rolling with global reset		rolling with global reset		rolling with global reset		
Shutter speed	0.049 - 603 ms	0.062 - 745 ms	0.02 - 394 ms	0.039 - 633 ms	0.09 - 2933 ms			0.046 - 860 ms		0.075 - 600 ms		0.056 ms - 21.8 s		0.085 ms - 89 s	0.074 ms - 77 s	0.146 ms - 135 s		
Dynamic range [dB]	55		68		71			62		71		62		61		70		65
Binning	2 x 2 / 4 x 4		-		2 x 2			2 x 2		2 x 2		2 x 2 / 4 x 4		2 x 2 / 4 x 4		2 x 2 / 4x4		
Skipping	-		640 x 512		640 x 512 / 320 x 256 multiple ROI's / user-defined			768 x 576 / 384 x 256		640 x 512 / 320 x 256 multiple ROI's / user-def.		1024 x 768 / 512 x 384		1280 x 960 / 640 x 448		1920 x 1344 / 960 x 640		
Aspect ratio	14:9		5:4		5:4			4:3		4:3		4:3		4:3		4:3		
Gain [dB]	12		23	24	24			24		24		18		18		18		
Lens	C- / CS-mount																	
Scanning system	progressive scan																	
Trigger	external / software																	
Strobe	yes																	
GPIO	3x																	
Interface	USB2.0 / 480 Mbps																	
Dimension (W x H x D) [mm]	industrial: 30 x 30.5 x 33 board: 28 x 28 x 22																	
USB connection	mini-B USB																	
Digital I/O connection	8 pin lockable																	
Power consumption [W]	< 1.0		< 1.0		< 1.0			< 1.5		< 1.0		< 1.5		< 1.5		< 1.5		
Operating temperature	0 to +45° C																	

APPLICATION & SOFTWARE

Ask us for matching lenses & illumination!

APPLICATION OVERVIEW

iCube targets industries in rough environments like quality inspection, completeness, surface and printing inspection, bar code, data matrix applications and others. Being also appropriate for non-industrial segments like medicine applications and microscopy, security, document management and access control, the small and efficient iCube is a versatile and reliable solution for your application requirements.


CAMERA CUSTOMIZATION

Particular applications require specific camera features and functions. To fulfill these requirements NET is able to offer camera customization, e.g. through onboard processing of specific available NET or customers' algorithms.

OEM APPLICATION

The iCube series is also available as small sized and lightweight board level cameras for OEM use. All advantages of the iCube camera plus additional customer requirements can be implemented


in a board camera e.g. customized firmware, FPGA/DDR RAM, real-time processing.



iCube customized solution with AUTOFOCUS lens

VIEWER SOFTWARE

The iControl viewer is a part of the provided software development kit (SDK) and enables an easy and quick access to all iCube cameras via Windows and LINUX for testing and evaluation. It allows a fast access to camera and image processing settings, and the creation of customer modes. iControl supports the possibility to save images as jpg, bmp or tiff as well as videos as avi file on a connected computer.



SOFTWARE DEVELOPMENT KIT (SDK)

The flexible SDK from NET makes the integration into existing and customized image capturing and processing systems simple. Programming samples are available for Microsoft Visual C++, Visual Basic and C#.

3RD PARTY SOFTWARE-APPLICATION

The integration of iCube USB cameras is supported through a wide variety of common drivers, e.g. for Cognex, and allows an easy handling of the camera. The iCube family is compatible to common software libraries with Direct-X/Direct-Show interface. The software allows an easy integration into commercial vision systems from suppliers like Halcon and Matrox.

NET New Electronic Technology GmbH

Lerchenberg 7
86923 Finning, Germany
Tel: +49 8806 9234 0
Fax: +49 8806 9234 77
info@net-gmbh.com
www.net-gmbh.com

NET Italia S.r.l.

Via Carlo Pisacane, 9
25128 Brescia, Italy
Tel: +39 030 5237 163
Fax: +39 030 5033 293
info@net-italia.it
www.net-italia.it

NET USA, Inc.

3037 45th Street
Highland IN 46322, USA
Tel: +1 219 934 9042
Fax: +1 219 934 9047
info@net-usa-inc.com
www.net-usa-inc.com

NET Japan Co., Ltd.

2F Shin-Yokohama 214 Bldg.
2-14-2 Shin-Yokohama, Kohoku-ku,
Yokohama-shi, 222-0033, Japan
Tel: +81 45 478 1020
Fax: +81 45 476 2423
info@net-japan.com
www.net-japan.com